

SAFETY DEVICE FOR STRIP  
DISPENSING MACHINE

5 The invention relates to the technical field  
of means of dispensing a predetermined length of  
strip material wound on a reel.

10 The invention applies to machines for the  
simultaneous dispensing and cutting of paper, wadding  
or wipe material in all hand-wipe or toilet paper  
dispensing applications.

15 The Applicant has developed many dispensing  
machines of this type which are defined, in  
particular, in European Patent 145 622.

20 A machine of this type comprises a housing  
having a parallelepiped configuration containing a  
drum rotatably mounted with respect to the lateral  
end shields of the housing, this drum being  
designed to internally accommodate a cutting  
mechanism with a serrated blade capable of moving  
out of the drum in a given cycle when the drum  
rotates as a result of the strip of paper being  
25 pulled by a user. A device to start and return the  
drum described in the Applicant's previous patent  
makes it possible to cut the strip of material  
cleanly.

30 The reel of material located above the drum is  
held by end shields located either side of the housing  
of the machine and may or may not rest on the drum.

35 The strip of material to be dispensed passes over  
the rear of the drum so that it can be dispensed through a  
slit in the lower part of the housing.

0996028-092801  
T02260-82099660

In order to ensure that the strip of paper or material pulled by the user is ejected from the machine along a satisfactory trajectory, the Applicant has made provision to design the drum with a groove which guides and accommodates an endless transmission belt which is wound around a shaft, said shaft being secured between the lateral sides of the housing and located close to the area of the opening through which the strip of paper is ejected from the bottom of the machine.

This shaft also has a groove which is located in close relationship and in the same plane as the groove on the drum so that, when the drum rotates in order to obtain cutting, said belt spins the shaft and correctly guides the strip of paper towards the outlet of the machine.

The arrangements of this type are described in the above-mentioned European Patent.

Although these arrangements ensure satisfactory operation of the paper strip dispensing machine, there are still nevertheless several drawbacks resulting from the way in which the strip of paper is fed and pulled through the outlet of the dispensing machine by the user.

In fact, the user often tends to pull the strip of paper to the right or left-hand side at a slant and this has the effect of causing the belt to escape from the above-mentioned grooves, thus impeding operation of the machine and sometimes jamming it if the paper tears.

Very often the belt even tends to jump out of the groove and this obviously has an adverse effect on the correct operation of the dispensing machine.

TOP SECRET 82099550

The first solution tried to solve these drawbacks was to increase the tension of the belt in order to prevent it escaping from the groove by keeping it very tight. This first solution had a secondary disadvantage. It was apparent that it became hard to rotate the mechanism for starting the drum and difficulties were encountered in pulling the paper and strip of material in general, especially when the user's hands were wet.

Increasing the tension of the belt was therefore unsatisfactory and made it impossible to use the dispensing machine.

Another approach was to increase the diameter of the edges of the groove on the shaft so as to produce a kind of deep channel intended to prevent the part of the belt in question from escaping if the paper was pulled sideways.

This solution was not entirely satisfactory because, in practice, it became apparent that the middle of the paper was marked and very often split in two pieces either side of the central area when it was cut.

The approach adopted by the Applicant was therefore to attempt to modify the drum/safety shaft connection so as to give a satisfactory solution to the problems encountered, associated with the user pulling the strip of paper emerging from the machine sideways, exerting a greater or lesser tensile force, so as to prevent the belt escaping from its groove.

According to a first aspect of the invention, the control and security device allowing ejection of

the strip of material from a strip dispensing machine comprising a drum and a safety shaft which shuts off the lower opening through which the strip of material passes as it leaves the housing and the drum, said drum and said shaft being linked by a means of transmission consisting of a belt, is characterised in that said transmission means is float mounted between the drum and the shaft, with the central part of the shaft that accommodates said belt and faces the groove on the drum being designed with a dolly axle configuration having a dimension that exceeds the width of the groove on the drum so as to allow sideways, slanting deflection of the belt over a limited amplitude, thus tracking the direction in which the strip of paper is pulled longitudinally out of the dispensing machine by the user.

These aspects and others will become apparent from the following description.

The object of the present invention is described, merely by way of example, in the accompanying drawings in which:

- Figure 1 is a side view of a machine for dispensing strips of material designed in accordance with the invention;
- Figure 2 is a plan cross-sectional view along line 2-2 in Figure 1;
- Figure 3 is a large-scale view of the shaft designed in accordance with the invention showing the position of the belt as a function of different frontal or lateral tensile forces.

In order that the present invention may more readily be understood, the following description is given, merely by way of example, reference being made to the accompanying drawings.

5

The dispensing machine is referred to in its entirety as (1). One particular embodiment is described below, merely by way of example, making it possible to adapt the invention.

10

It comprises a wall-mounted housing (2) having lateral sides or end shields (3) capable of accommodating an internally hollow rotating drum (4) on their lower part.

15

This drum is capable of accommodating a cutting mechanism (5) capable of moving out of said drum when the drum rotates as the strip of paper is pulled so that said strip of paper can be cut.

20

The cutting mechanism can be of the type described in the Applicant's patents.

25

The internally hollow drum has a slit (4a) through which the cutting device (5) emerges from the drum.

30

Laterally and in a known manner, the drum can accommodate a start mechanism (7) of the previously described type.

35

The strip of material wound on the reel is mounted between the upper end shields (8) so that said reel advantageously rests against the drum.

5

10

15

20

25

35

in order to ensure lateral deflection depending on the way in which the strip of paper is pulled.

Advantageously, the dolly axle (9a) shape of the above-mentioned part of the shaft is laterally locked by the walls (9b) of the shaft (9) thus forming a shoulder and limit stop so that said belt cannot escape from its groove. The float-mounted belt nevertheless remains held in its extreme position against one of the inside walls of the shaft, it does not jump out and does not move onto the outer periphery (9c) of the latter.

This float mounting and limited deflection amplitude of the transmission belt between the drum and the safety shaft makes it possible to use the dispensing machine in any situations where the strip of material is pulled sideways without the machine thereby being jammed.

In addition and incidentally, the groove (4a) on the drum may have, in the location of the slit formed in the drum, a slight extra thickness (4b) to ensure control of the position of the transmission belt during extreme deflection of the float-mounted belt along the dolly axle shape of the safety shaft.

The invention is applicable to all types of machines for dispensing strips of material which include connection by means of belt-type transmission between the drum that accommodates a cutting device and a safety shaft located in the lower part of the housing which ensures guided ejection of the strip of material.

0996028-02201  
"02260" 82099560

5

10

15

25

35